



H62 TRASPARENTE 2K ANTI-SCRATCH

"Special Finish" two-pack acrylic clear coat

A) DESCRIPTION AND FIELDS OF APPLICATION:

Acrylic clear coat for double layer painting systems. Scratch and wear resistant.
Excellent adhesion on waterborne or solvent base coats; easy to apply and fast drying.
Product rated as a "Special Finish" with VOC = 600 g/l, compliant with the limit for the category set by Directive 2004/42 EC.

B) TECHNICAL DATA:

Composition:	Hydroxylated acrylic resins
Specific weight:	0.96 ± 0.03
Available colours:	Colourless, transparent
Safety data:	Refer to the safety sheet

C) PREPARATION DU SUPPORT:




- * Matt base coat for two coats of solvent-based paint
- * Matt base coat for two coats of water-based paint

D) CAUTIONS:

- * Two component acrylic paints are affected by moisture.
- * Comply with the dilution stated.
- * Do not use the product at temperatures below 5°C.
- * Keep in a cool, dry place.



E) PROCESSING:



2:1 hardener C01-C02-C03 potlife > 60' at 20°C.




5-10% with D10-11 thinner
15"-14" DIN 4 mm at 20°C



1.2-1.3 mm 3.5-5 bar
1-2 = 40-45 micron



1.4-1.5 mm 3.5-5 bar
1-2 = 40-45 micron



10'-15' drying depending on temperature



4 h at 20°C
20' at 60°C



10'-15' at 1 mt.

F) TOOLS CLEANING:

* With thinner for polyurethane products

G) RECOATING :

Technical indications and advices are based on our own experiences. We assure the perfect quality of products. However, being the utilization out of our control, we assume no responsibility on the results obtained